



产品承认书

SPECIFICATION FOR APPROVAL

客户名称:

CUSTOMER

我司料号:

OUR PART NO.

XRACM4532A-421D-2PT

我司品名:

OUR PART NAME

Common mode choke

送样日期:

DATE SAMPLES

数量:

QUANTITY

制造确认 MANUFACTURER APPROVE

拟制 DRAWN	审核 CHECKED	确认 APPROVED
Hu Fangting	RaoPing	LiZhengxiong

客户确认 CUSTOMER APPROVE

客户名称 CUSTOMER NAME:

客户料号 CUSTOMER P/N:

规格型号 DESCRIPTION:

ACM4532A 420Ω 3.36A

检查结果: ☐ 合格 ☐ 不合格

签名及盖章:

INSPECT RESULT ACCEPT REJECT

SIGNATURE AND STAMP

说明 REMARK:

如对本承认书内容有异议请提出或标记发送至我司, 本承认书在未收到异议回复时于本承认书提供一周后生效。

If you have any objection to the contents of this acknowledgment, please raise it or send the mark to us. The acknowledgment will become effective one week after the acknowledgment is provided in the absence of any objection.

东莞市样如电子有限公司

DONGGUAN XIANGRU ELECTRONICS CO., LTD

Tel: 0769-86346548 Fax: 0769-86346358

Email: dgxiangru@126.com


产品承认书

SPECIFICATION FOR APPROVAL

客户名称 CUSTOMER		日期 DATE	2024/6/21
客户物料编号 CUSTOMER P/N		客户规格型号 DESCRIPTION	ACM4532A 420Ω 3.36A
我司物料编号 OUR PART NO	XRACM4532A-421D-2PT	我司品名 OUR PART NAME	Common mode choke



外观尺寸 Appearance of size

单位 Unit: mm





Part No.	A	B	C	D	E	F
XRACM4532A	4.5 ± 0.2	3.2 ± 0.2	2.8 ± 0.2	0.2 ± 0.1	1.2Typ.	1.0Typ.


Recommended Footprint(mm):



Tape Dimensions(Unit:mm):



SEC. B-B'



SEC. A-A'

Size	A0	B0	K0	W	E	F	P0	P1	D0
XRACM4532A	4.90 ± 0.10	3.45 ± 0.10	3.05 ± 0.10	12.00 ± 0.20	1.75 ± 0.10	5.50 ± 0.05	4.0 ± 0.05	8.0 ± 0.10	1.5 ± 0.1, -0




产品承认书
SPECIFICATION FOR APPROVAL

客户名称 CUSTOMER		日期 DATE	2024/6/21
客户物料编号 CUSTOMER P/N		客户规格型号 DESCRIPTION	ACM4532A 420Ω 3.36A
我司物料编号 OUR PART NO	XRACM4532A-421D-2PT	我司品名 OUR PART NAME	Common mode choke

电性能参数Electrical Performance Parameters:

Part No.	Z(Ω) Common Mode Impedance	Test Frequency	电阻DCR (Ω) [Max]	额定电流 Rated current Idc (A) [Max]	Rated Voltage Vdc (V) Typical	Insulation Resistance IR (MΩ) Min.
XRACM453 2A-421D- 2PT	420	100MHz	0.055	3.36	50	10

RECOMMENDED SOLDERING TEMP. GRAPH:



General Description: 一般说明

1. 工作温度:-25至+85℃;

Operating temperature : -25 to +85℃.

2. 储存温度和湿度:-40至+85℃, 最大70%RH;

Storage temp. and humidity : -40 to +85℃ , 70%RH max.

3. 典型的热额定值直流电流会导致大约 40C的AT。

Typical Heat Rating DC Current would cause an approximately ΔT of 40℃.

4. 如果使用波峰焊接, 会有一些风险。再流焊接温度低于 240度, 会有翘曲的风险;

If Use Wave soldering is there will be some risk. Re-flow soldering temperatures below 240 degrees, there will be unwitting risk.

制表 MADE	审核 CHECKED	批准 APPROVED	
Hu Fangting	RaoOing	LiZhengxiong	