



产品承认书

SPECIFICATION FOR APPROVAL

客户名称:

CUSTOMER

我司料号:

OUR PART NO.

XRPAEE5.0 Series

我司品名:

OUR PART NAME

Outgassing Compliant Current Sensors

送样日期:

DATE SAMPLES

数量:

QUANTITY

制造确认 MANUFACTURER APPROVE

拟制 DRAWN	审核 CHECKED	确认 APPROVED
Hu Fangting	RaoPing	LiZhengxiong

客户确认 CUSTOMER APPROVE

客户名称 CUSTOMER NAME:

客户料号 CUSTOMER P/N:

规格型号 DESCRIPTION:

XRPAEE5.0 Series

检查结果: ☐ 合格 ☐ 不合格

签名及盖章:

INSPECT RESULT ACCEPT REJECT

SIGNATURE AND STAMP

说明 REMARK:

如对本承认书内容有异议请提出或标记发送至我司, 本承认书在未收到异议回复时于本承认书提供一周后生效。

If you have any objection to the contents of this acknowledgment, please raise it or send the mark to us. The acknowledgment will become effective one week after the acknowledgment is provided in the absence of any objection.

东莞市祥如电子有限公司

DONGGUAN XIANGRU ELECTRONICS CO., LTD

Tel: 0769-86346548 Fax: 0769-86346358

Email: dgxiangru@126.com

SMTEE5.0 SERIES






Outgassing Compliant Current Sensors

Applications:

- .Switching power supplies
- .Feedback control.
- .Overload sensing.
- .Load drop/shut down detection.



Shape and Dimensions (Dimensions are in mm):



Features:

- .Very low DC resistance.
- .Different turns ratios.
- .Small package.
- .Other pinning on request.

Product Identification :

XRPAEE5.0-1-100TNL

1 2 3 4

(1) Type: Surface Mountable Type.

(2) Style:EE Core,5.0 is size.

(3)The primary turns :1T

(4) Secondary turns:100T

产品承认书

SPECIFICATION FOR APPROVAL

Characteristics:

- .Temperature Rise Current(Irms):The current when emperature of coil increases up to max.oT=40C.(Ta=20 °C)
- . Operating temperature :-40Cto125C.

Test equipments:

- .L: HP4284A PRECISION LCR METER
- .DCR: CHENHWA 502 OHM METER
- .Electrical specifications at 25C.

SMTEE5.0 series

Part No.	Turns ratio pri: sec	Secondary Inductance @100KHZ0.1V (uH)MIN	DCR (Ω)		Primary Current (A) (Max)
			Sec Max	Pri Ref	
XRPAEE5.0-1-20TNL	1:20	80	0.40	0.0007	10/20.5
XRPAEE5.0-1-30TNL	1:30	180	0.87	0.0007	10/20.5
XRPAEE5.0-1-40TNL	1:40	320	1.14	0.0007	10/20.5
XRPAEE5.0-1-50TNL	1:50	500	1.85	0.0007	10/20.5
XRPAEE5.0-1-60TNL	1:60	730	2.30	0.0007	10/20.5
XRPAEE5.0-1-70TNL	1:70	980	4.75	0.0007	10/20.5
XRPAEE5.0-1-100TNL	1:100	2000	5.50	0.0007	10/20.5
XRPAEE5.0-1-125TNL	1:125	3000	11.50	0.0007	10/20.5

SMTEE5.0 Temp Risevs Current

