



# 产品承认书 SPECIFICATION FOR APPROVAL

客户名称:  
CUSTOMER

我司料号:  
OUR PART NO.

XRR6\*15

我司品名:  
OUR PART NAME

bar magnet

送样日期:  
DATE SAMPLES

数量: 0PCS  
QUANTITY

## 制造确认 MANUFACTURER APPROVE

拟制 DRAWN	审核 CHECKED	确认 APPROVED
HuFangting	RaoPing	ZhongCuilan

## 客户确认 CUSTOMER APPROVE

客户名称 CUSTOMER NAME:

客户料号 CUSTOMER P/N:

规格型号 DESCRIPTION:

R6\*15

检查结果:  合格  不合格

签名及盖章:

INSPECT RESULT ACCEPT REJECT

SIGNATURE AND STAMP

说明 REMARK:

如对本承认书内容有异议请提出或标记发送至我司，本承认书在未收到异议回复时于本承认书提供一周后生效。

If you have any objection to the contents of this acknowledgment, please raise it or send the mark to us. The acknowledgment will become effective one week after the acknowledgment is provided in the absence of any objection.

东莞市祥如电子有限公司

DONGGUAN XIANGRU ELECTRONICS CO., LTD

Tel: 0769-86346548 Fax: 0769-86346358

Mailbox: dgxiangru@126.com


<b>详述</b> give exact information	<b>符合</b> accord with
----------------------------------	-----------------------

客户client		表号 second name	2 (1)
品名name of an article	铁氧体磁芯ferrite core	sample name	XRR6*15
批号 batch number			


1 产品标识production label

XRR    6\*    15  
1        2        3

- (1) 型号model
- (2) 外径outside diameter
- (3) 高度height



2 尺寸measure



序号NO	Measure (mm)	
A	6.00	±0.3
B	15.00	±0.4
C		
D		
E		
F		
G		
H		
I		

3. 电气性能测试指标 Electrical performance test index

No.	特点characteristic		Standard value	单位unit	误差tol.
	test condition				
1	1KHZ/0.3V	L	0.5	uH	MIN
	居里温度	TC	180	度	最大

Naming Method	测试test	审核check	批准approve

## 详述 give exact information

客户client		表号second name	
品名name of an article	铁氧体磁芯 ferrite core	样品名称 sample name	XRR6*15
批号batch number			

### 9. 检测条件Detection condition

检测仪器：CH-1062电感测试

测试条件：∅ 2.3mm /3.5TS

温度：25° C      湿度：60%

1	电气特性electrical specification	尺寸measure		
配置 deploy	电感(uH)		外径outside diameter (A)	高度height (B)
标准 standard	0.5uh ± 20%		6.00 ±0.3	15.00 ±0.4
1	0.46		5.95	15.01
2	0.53		5.97	14.89
3	0.54		5.94	14.97
4	0.51		5.98	15.01
5	0.49		5.96	15.20
6	0.48		5.94	15.11
7	0.49		5.97	15.08
8	0.50		5.94	15.12
9	0.51		5.95	15.05
10	0.52		5.96	15.09
X	0.50		5.96	15.05
R	0.08		0.04	0.14

备注  
remarks

	测试test	审核check	批准approve