



产品承认书 SPECIFICATION FOR APPROVAL

客户名称:

CUSTOMER

我司料号:

OUR PART NO.

XRDC108075-R20L-K

我司品名:

OUR PART NAME

MOLDING POWER INDUCTORS

送样日期:

DATE SAMPLES

数量:

QUANTITY

制造确认 MANUFACTURER APPROVE

拟制 DRAWN	审核 CHECKED	确认 APPROVED
HuFangting	RaoPin	Zhongcuilan

客户确认 CUSTOMER APPROVE

客户名称 CUSTOMER NAME:

客户料号 CUSTOMER P/N:

规格型号 DESCRIPTION: XRDC108075 0.2uH ±15% 50A

检查结果: 合格 不合格

签名及盖章:

INSPECT RESULT ACCEPT REJECT

SIGNATURE AND STAMP

说明 REMARK:

如对本承认书内容有异议请提出或标记发送至我司, 本承认书在未收到异议回复时于本承认书提供一周后生效。

东莞市祥如电子有限公司

Dongguan xiangru electronics co., ltd

Tel: 0769-86346548 Fax: 0769-86346358


Email: dgxiangru@126.com

产品承认书

SPECIFICATION FOR APPROVAL

客户名称 CUSTOMER		日期 DATE	2025/9/10
客户物料编号 CUSTOMER P/N		客户规格型号 DESCRIPTION	XRDC108075 0.2uH ±15% 50A
我司物料编号 OUR PART NO	XRDC108075-R20L-K	我司品名 OUR PART NAME	MOLDING POWER INDUCTORS

外观尺寸 Appearance of size
单位 Unit: mm



A	10.2±0.2	C	7.3±0.2	E	2.54±0.5
B	8.0MAX	D	2.2±0.2	F	
标识 Identification					

ELECTRICAL CHARACTERISTIC:

L(μH) :	0.20±15% 100KHz 1.0V
DCR(mΩ):	0.29±6% 0.29 (Typ.) (@25°C)
Isat(A):	50.0 Typ.(L 50.0A/L0A*100%≈80%)@25°C
Isat(A):	40.0 Typ.(L 40.0A/L0A*100%≈80%)@100°C
INDUCTANCE Drop Approximately:	20% .@ IDC 12A
Irms(A):	56.0 Typ. (ΔT°C)≈40°C

Use Frequency Range: 5.1 MHz (REF)


Operating Temperature Range: -40°C ~+125°C

SCHEMATIC DRAWING



Equivalent Circuit

PCB PATTERN



G : 4.70 m/m (REF)
H : 2.50 m/m (REF)
I : 3.00 m/m (REF)

MATERIAL LIST:

NO	ITEM	MATERIAL	SUPPLIER OF THE MATERIAL
1	CORE		
2	BLAK		
3	COPPER		
4	COATING		
5	MARKING		




产品承认书 SPECIFICATION FOR APPROVAL

客户名称 CUSTOMER		日期 DATE	2025/9/10
客户物料编号 CUSTOMER P/N		客户规格型号 DESCRIPTION	XRDC108075 0.2uH ±15% 50A
我司物料编号 OUR PART NO	XRDC108075-R20L-K	我司品名 OUR PART NAME	MOLDING POWER INDUCTORS

TYPICAL ELECTRICAL CHARACTERISTICS

INDUCTANCE VS CURRENT@100KHZ/1.0V

IDC	0A	10A	20A	30A	40A	50A	60A			
L (μH) @25°C	0.2	0.199	0.194	0.19	0.188	0.183	0.178			
L (μH) @100°C	0.206	0.203	0.2	0.196	0.193	0.188	0.018			






产品承认书 SPECIFICATION FOR APPROVAL

客户名称 CUSTOMER		日期 DATE	2025/9/10
客户物料编号 CUSTOMER P/N		客户规格型号 DESCRIPTION	XRDC108075 0.2uH ±15% 50A
我司物料编号 OUR PART NO	XRDC108075-R20L-K	我司品名 OUR PART NAME	MOLDING POWER INDUCTORS

TYPICAL ELECTRICAL CHARACTERISTICS

INDUCTANCE VS CURRENT@100KHZ/1.0V

IDC	0A	5A	10A	15A	20A	25A	30A	35A	40A	45A	50A	55A	60A
ΔT(°C)	0.0	0.5	0.9	1.8	3.1	5.6	9.30	14.7	20.2	26	31.5	37.5	44.90






产品承认书
SPECIFICATION FOR APPROVAL

客户名称 CUSTOMER		日期 DATE	2025/9/10
客户物料编号 CUSTOMER P/N		客户规格型号 DESCRIPTION	XRDC108075 0.2uH ±15% 50A
我司物料编号 OUR PART NO	XRDC108075-R20L-K	我司品名 OUR PART NAME	MOLDING POWER INDUCTORS

L Frequency characteristics


Hz(KHz)	10	100	300	500	800	1000	2000	3000	4000	5000	5100	6000	7000	8000
L (μH)	0.198	0.2	0.182	0.183	0.183	0.185	0.187	0.182	0.174	0.163	0.16	0.129	0.102	0.068
		100%	91.00%	91.5%	91.5%	92.5%	93.5%	91.0%	87.0%	81.5%	80.0%	64.5%	51.0%	34.0%



产品承认书





SPECIFICATION FOR APPROVAL

客户名称 CUSTOMER		日期 DATE	2025/9/10
客户物料编号 CUSTOMER P/N		客户规格型号 DESCRIPTION	XRDC108075 0.2uH ±15% 50A
我司物料编号 OUR PART NO	XRDC108075-R20L-K	我司品名 OUR PART NAME	MOLDING POWER INDUCTORS
TEST ITEMS	SPECIFICATIONS	TEST CONDITIONS / TEST METHODS	
ELECTRICAL PERFORMANCE TEST			
L	REFER TO STANDARD ELECTRICAL CHARACTERISTIC LIST.	MICROTEST6377	
DCR		TH2511	
RATED CURRENT		APPLIED THE CURRENT TO COILS THE INDUCTANCE CHANGE SHOULD BE LESS THAN 30% TO INITIAL VALUE AND TEMPERATURE RISE SHOULD NOT BE 40°C TYPICAL	
TEMPERATURE RISE TEST	40°C MAX (Δt)	1. APPLIED THE ALLOWED DC CURRENT FOR 4 HOURS. 2. TEMPERATURE MEASURE BY DIGITAL SURFACE THERMOMETER.	
OVER LOAD TEST	NO EVIDENCE OF ELECTRICAL DAMAGE	APPLIED 1.5 TIMES OF RATED ALLOWED DC CURRENT TO INDUCTORS FOR A PERIOD OF 5 MINUTES.	
MECHANICAL PERFORMANCE TEST			
SOLDER HEAT RESISTANCE	1. INDUCTORS SHOULD HAVE NO EVIDENCE OF ELECTRICAL AND MECHANICAL DAMAGE 2. INDUCTANCE SHOULD NOT CHANGE MORE THAN ±10%	PREHEAT: 150°C 100s Max. SOLDER TEMPERATURE: 255±5°C DIP TIME: 10s Max.	
VIBRATION TEST (LOW FREQUENCY)		1. AMPLITUDE: 1.5 mm 2. FREQUENCY: 10-55-10HZ / 1 MIN 3. DIRECTION: X, Y, Z 4. DURATION: 2 HRS/X, Y, Z	
SHOCK TEST		INDUCTORS SHOULD BE DROPPED 10 TIMES FROM A HEIGHT OF 1m ONTO 3cm WOODEN BOARD.	



产品承认书

SPECIFICATION FOR APPROVAL

客户名称 CUSTOMER		日期 DATE	2025/9/10
客户物料编号 CUSTOMER P/N		客户规格型号 DESCRIPTION	XRDC108075 0.2uH ±15% 50A
我司物料编号 OUR PART NO	XRDC108075-R20L-K	我司品名 OUR PART NAME	MOLDING POWER INDUCTORS
TEST ITEMS	SPECIFICATIONS	TEST CONDITIONS / TEST METHODS	
MECHANICAL PERFORMANCE TEST			
SOLDERABILITY TEST	MORE THAN 90% OF TERMINAL ELECTRODE SHOULD BE COVERED WITH SOLDER.	PREHEAT:150 °C 120x SOLDER BATH AT 255±5°C DIP TIME:10s Max.	 <p style="font-size: small;">255°C 183°C 150°C 10s Max. Natural cooling 50±10s Time (s)</p>
COMPONENT ADHESION (PUSH TEST)	1.5Kg Min	THE DEVICE SHOULD BE REFLOW SOLDERED (255±5°C FOR 10 SECONDS) TO A TINNED COPPER SUBSTRATE. A DYNAMETER FORCE GAUGE SHOULD BE APPLIED TO THE SIDE OF THE COMPONENT. THE DEVICE MUST WITH- STAND A MINIMUM FORCE OF 1.5Kg WITHOUT AILURE OF THE TERMINATION .	 <p style="font-size: x-small;">FOLDED GLASS CRIST SUBSTRATE WITH COPPER SLAG DIP IN SOLDER BATH</p>
COMPONENT ADHESION (PULL TEST)	1.5Kg Min	1.INSERT 10cm WIRE INTO THE REMAINING OPEN EYE BEND THE ENDS OF EVEN WIRE LENGTHS UPWARD AND WIND TOGETHER 2. TERMINAL SHALL NOT BEREMARKABLY DAMAGED	
FLEXTURE STRENGTH	THE FORCES APPLIED SHOULD NOT DAMAGE THE DIELECTRIC.	SOLDER A CHIP ON A TEST SUBSTRATE, BEND THE SUBSTRATE BY 2mm AND RETURN.	 <p style="font-size: x-small;">Bending 45mm 45mm 40mm 100mm</p>
RESISTANCE TO SOLVENT TEST	THERE SHOULD BE NO CASEDEFORMATION, CHANGE IN APPEARANCE OR BITERATION OF MARKING	INDUCTERS SHALL WITHSTAND 6 MINTES OF ALCOHOL	




产品承认书 SPECIFICATION FOR APPROVAL

客户名称 CUSTOMER		日期 DATE	2025/9/10
客户物料编号 CUSTOMER P/N		客户规格型号 DESCRIPTION	XRDC108075 0.2uH ±15% 50A
我司物料编号 OUR PART NO	XRDC108075-R20L-K	我司品名 OUR PART NAME	MOLDING POWER INDUCTORS

TEST ITEMS	SPECIFICATIONS	TEST CONDITIONS / TEST METHODS
------------	----------------	--------------------------------

CLIMATIC TEST

TEST ITEMS	SPECIFICATIONS	TEST CONDITIONS / TEST METHODS
TEMPERATURE CHARACTERISTIC	1.APPEARANCE:NO DAMAGE 2.INDUCTANCE:WITHIN±10% OF INITIAL VALUE.	(-55℃ ~ +125℃)
HUMIDITY TEST		60℃±2℃ / 96±2 HOURS R.H:90-95%RH
LOW TEMPERATURE STORAGE		1.TEMPERATURE:-55℃±2℃ 2.TIME: 96±2 HOURS
THERMAL SHOCK TEST		1.-55±5℃ FOR 30 MINUTES. +125±5℃ FOR 30 MINUTES. 2.TOTAL: 10 CYCLES
HIGH TEMPERATURE STORAGE		1.APPLIED CURRENT: MAX RATED CURRENT 2.TEMPERATURE:120℃±2℃



NOTE: INDUCTORS ARE TO BE TESTED AFTER 2 HOUR AT ROOM TEMPERATURE.


LIFE TEST

TEST ITEMS	SPECIFICATIONS	TEST CONDITIONS / TEST METHODS
HIGH TEMPERATURE LOAD LIFE TEST	INDUCTORS SHOULD BE NO EVIDENCE OF SHORT OR OPEN CIRCUIT	1. TEMPERATURE: 125±2℃ 2. TIME: 500±12 HOURS 3. LOAD: ALLOWED DC CURREN
HUMIDITY LOAD LIFE TEST		1. TEMPERATURE: 60±2℃ 2. R.H.: 90-95% 3. TIME: 500±12 HOURS 4. LOAD: ALLOWED DC CURREN

产品承认书 SPECIFICATION FOR APPROVAL

客户名称 CUSTOMER		日期 DATE	2025/9/10
客户物料编号 CUSTOMER P/N		客户规格型号 DESCRIPTION	XRDC108075 0.2uH ±15% 50A
我司物料编号 OUR PART NO	XRDC108075-R20L-K	我司品名 OUR PART NAME	MOLDING POWER INDUCTORS

REFLOW PROFILE



Lead-Free(LF)标准温度分析范围

项目 Item	升温区 Ramp-up	预热区 Pre-heating	焊锡区 Reflow	PeakTemp	冷却区 Cooling
温度范围 Temp Scope	R.T. -150°C	150-200°C	220°C	260±5°C	6°C/sec Max
标准时间 Time spec	-	60-180 sec	60-150 sec	20-40 sec	-

Note:

1. Re-flow possible times: within 2 time
2. Nitrogen adopted is recommended while in re-flow


Iron Soldering Profile

Iro soldering power:Max.30W

Pre-heating:150 °C/60sec

Soldering time:3sec.Max. Solder paste:Sn/3.0Ag/0.5Cu

Max.1 times for iron soldering




产品承认书 SPECIFICATION FOR APPROVAL

客户名称 CUSTOMER		日期 DATE	2025/9/10
客户物料编号 CUSTOMER P/N		客户规格型号 DESCRIPTION	XRDC108075 0.2uH ±15% 50A
我司物料编号 OUR PART NO	XRDC108075-R20L-K	我司品名 OUR PART NAME	MOLDING POWER INDUCTORS

Packaging Specification (卷轴尺寸):

REEL DIMENSIONS

STYLE	REEL DIMENSIONS(m/m)						
	QTY(PCS)	A	B±0.8	C±0.5	G	N	T
108075	700	330	21	13	24.5	100	29





载带尺寸 Tape Dimension:



•载带尺寸, 印字方向, 印字内容的第一个字对定位孔(如图所示)

word pair orifice of printed content (as shown) .

Tape size, printing direction, first



材质	下带颜色	上带颜色	封带方式(冷/热)	拉力(g)	W±0.3	A0±0.1	B0±0.1	K0±0.1	P±0.1	T1±0.05	ØD±0.1/-0	E±0.1	F±0.1	P2±0.1	P0±0.1
透明 PS	透明	透明	热	20-120	24	8.0	10.3	7.7	12	0.4	1.5	1.75	11.5	2	4



包装方法参照国际标准 IEC 60286 -3: 2013

Packaging is referred to the international standard IEC 60286 -3:2013

THE PEEL FORCE WITH A PEEL SPEED OF 300mm/MIN±10mm/MIN SHALL BE AS FOLLOWS: 0.1N TO 1.0N FOR AN 8mm TAPE WIDTH. 0.1N TO 1.3N FOR A 12mm~56mm TAPE WIDTH

产品承认书
SPECIFICATION FOR APPROVAL

客户名称 CUSTOMER		日期 DATE	2025/9/10
客户物料编号 CUSTOMER P/N		客户规格型号 DESCRIPTION	XRDC108075 0.2uH ±15% 50A
我司物料编号 OUR PART NO	XRDC108075-R20L-K	我司品名 OUR PART NAME	MOLDING POWER INDUCTORS



PACKAGE:

卷轴包装数量
每卷 700 PCS

注意: 标签贴在载带无孔侧胶盘面标签位置, 载带两边有孔贴在载带圆孔侧胶盘面标签位置

LABEL
标签
ROLL带轴


CARRIER TAPE
包装带



内盒包装数量
每盒 2 卷, 共 1400 PCS

Inner Box Dimension: 34*34*6.5cm

外箱包装数量
每箱 2 盒, 共 2800 PCS



Carton Dimension: 36.5*35.5*14.5cm

Storage Conditions

- *Temperature and humidity conditions: Less than 40°C and 70% RH.
- *Recommended products should be used within 6 months form the time of delivery.
- *The packaging material should be kept where no chlorine or sulfur exists in the air.

Transportation

- *Products should be handled with care to avoid damage or contamination from perspiration and skin oils.
- *The use of tweezer or vacuum pick up is strongly recommended for individual components.
- *Bulk handing should ensure that abrasion and mechanical shock are minimized.